


HAK

- Body construction Hak 2"-24"
- Face to face EN 558-1/ ISO 5752 series 14/15 (DIN 3202 F4/F5)
EN 1092-2 (ISO 7005-2) PN 10
- Max working pressure PN 16
- Temperature range -20°C + 140°C according to material
- Operation Handwheel
T key
Electric actuator
- Coating Standard: Plascoat PPA 571 AQUA
Optional: Epoxy/ Rilsan (Nylon 11)/ Enamel (internal)
- Flanges acc. to EN 1092-2 (ISO 7005-2) PN 10/PN 16
AS 4087 (BS Table D)



Materials

Item	Description	Material
1	Body	Ductile Iron
2	Wedge	Ductile Iron + EPDM
3	Stem	SS
4	Bonnet gasket	NBR
5	Bolts	SS
6	Stem Nut	Copper Alloy
7	Bonnet	Ductile Iron
8,11,12	O-rings	NBR
9	Holding Ring	Copper Alloy
10	Gland	Ductile Iron
13	Handwheel (optional)	Ductile Iron



Dimensions

mm	50	65	80	100	125	150	200	250	300	350	400	450	500	600
inches	2"	2.5"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	24"
L (F4)	150	170	180	190	200	210	230	250	270	290	310	330	350	390
L (F5)	250	270	280	300	325	350	400	450	500	550	600	650	700	800
D (EN 1092-2 PN 10)	165	185	200	220	250	285	340	395	445	505	565	615	670	780
D (EN 1092-2 PN 16)	165	185	200	220	250	285	340	405	460	520	580	640	715	840
D (ANSI B16.1/B16.42)	152	178	191	229	254	279	343	406	483	533	597	635	699	813
D (AS4087(BS 10 Table D))	-	-	185	215	-	280	335	405	455	525	580	640	705	825
H	220	255	280	320	355	400	510	600	685	810	900	985	1065	1265
M (optional)	200	200	254	254	315	315	315	406	406	500	500	500	650	650

